


Material Safety Data Sheet

Gasoline, Unleaded



HMIS III:

| | |
|--------------|---|
| HEALTH | 1 |
| FLAMMABILITY | 3 |
| PHYSICAL | 0 |

0 = Insignificant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

| | | | | | |
|--------------------------------|---|--|-------------------------------------|---|----------------|
| Product name | : | Gasoline, Unleaded | | | |
| Synonyms | : | Blend of Highly Flammable Petroleum Distillates, Regular, Mid-Grade, Premium, 888100005481 | | | |
| MSDS Number | : | 888100005481 | Version | : | 2.9 |
| Product Use Description | : | Fuel | | | |
| Company | : | Tesoro Hawaii Corporation 300 Concord Plaza Drive, San Antonio, TX 78216-6999 | | | |
| Tesoro Call Center | : | (877) 783-7676 | Chemtrec (Emergency Contact) | : | (800) 424-9300 |

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

- Regulatory status** : This material is considered hazardous by the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).
- Hazard Summary** : Extremely flammable. Irritating to eyes and respiratory system. Affects central nervous system. Harmful or fatal if swallowed. Aspiration Hazard.

Recent preliminary reports suggest that the government-mandated ethanol component may not be compatible with fiberglass gasoline tanks. Ethanol may dissolve fiberglass resin, causing engine damage and possibly allow leakage of explosive gasoline.

Potential Health Effects

- Eyes** : Causes eye irritation.
- Skin** : May cause skin irritation. Can be absorbed through skin.
- Ingestion** : Aspiration hazard if liquid is inhaled into lungs, particularly from vomiting after ingestion. Aspiration may result in chemical pneumonia, severe lung damage, respiratory failure and even death. Ingestion may cause gastrointestinal disturbances, including irritation, nausea, vomiting and diarrhea, and central nervous (brain) effects similar to alcohol intoxication. In severe cases, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death may occur.
- Chronic Exposure** : Long-term exposure may cause effects to specific organs, such as to the liver, kidneys, blood, nervous system, and skin. Contains benzene, which can cause

blood disease, including anemia and leukemia.

Target Organs

: Eyes, Skin, Central nervous system, Liver, Kidney, Blood

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | CAS-No. | Weight % |
|--|------------|-------------|
| Gasoline, natural; Low boiling point naphtha | 8006-61-9 | 10 - 30% |
| Toluene | 108-88-3 | 10 - 30% |
| Xylene | 1330-20-7 | 10 - 30% |
| Ethanol; ethyl alcohol | 64-17-5 | 0-8.2% |
| Trimethylbenzene | 25551-13-7 | 1 - 5% |
| Isopentane; 2-methylbutane | 78-78-4 | 1 - 5% |
| Naphthalene | 91-20-3 | 1 - 5% |
| Benzene | 71-43-2 | 0.1 - 4.7% |
| Pentane | 109-66-0 | 1 - 5% |
| Cyclohexane | 110-82-7 | 1 - 5% |
| Ethylbenzene | 100-41-4 | 1 - 5% |
| Butane | 106-97-8 | 1 - 20% |
| Heptane [and isomers] | 142-82-5 | 0.5 - 0.75% |
| N-hexane | 110-54-3 | 0.5 - 0.75% |

SECTION 4. FIRST AID MEASURES

| | |
|---------------------|--|
| Inhalation | : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention immediately. |
| Skin contact | : In case of contact, immediately flush skin with plenty of water. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Contaminated leather, particularly footwear, must be discarded. Note that contaminated clothing may be a fire hazard. Seek medical advice if symptoms persist or develop. |
| Eye contact | : Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice if symptoms persist or develop. |
| Ingestion | : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Obtain medical attention. |

Notes to physician : Symptoms: Dizziness, Discomfort, Headache, Nausea, Kidney disorders, Liver disorders, Aspiration may cause pulmonary edema and pneumonitis. Lung edema.

SECTION 5. FIRE-FIGHTING MEASURES

Form : Liquid

Flash point : -45 °C (-49 °F)

Auto Ignition temperature : 257.22 °C (495.00 °F)

Lower explosive limit : 1.3 %(V)

Upper explosive limit : 7.6 %(V)

Suitable extinguishing media : SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO2, water spray, fire fighting foam, or Halon. LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers., Keep containers and surroundings cool with water spray.

Specific hazards during fire fighting : Extremely flammable liquid and vapor. This material is combustible/flammable and is sensitive to fire, heat, and static discharge.

Special protective equipment for fire-fighters : Firefighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full facepiece and full protective clothing.

Further information : Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam. Exposure to decomposition products may be a hazard to health. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Evacuate personnel to safe areas. Ventilate the area. Remove all sources of ignition. Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

Environmental precautions : Discharge into the environment must be avoided. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

CERCLA Hazardous substances and corresponding RQs :

| | | |
|--|-----------|-----------|
| Gasoline, natural; Low boiling point naphtha | 8006-61-9 | 100 lbs |
| Xylene | 1330-20-7 | 100 lbs |
| Toluene | 108-88-3 | 1,000 lbs |
| Ethanol; Ethyl alcohol | 64-17-5 | 100 lbs |
| Isopentane; 2-Methylbutane | 78-78-4 | 100 lbs |
| Naphthalene | 91-20-3 | 100 lbs |
| Benzene | 71-43-2 | 10 lbs |
| Pentane | 109-66-0 | 100 lbs |
| Ethylbenzene | 100-41-4 | 1,000 lbs |
| Cyclohexane | 110-82-7 | 1,000 lbs |
| Butane | 106-97-8 | 100 lbs |
| Heptane [and isomers] | 142-82-5 | 100 lbs |
| n-hexane | 110-54-3 | 5,000 lbs |

SECTION 7. HANDLING AND STORAGE

- Handling** : Keep away from fire, sparks and heated surfaces. No smoking near areas where material is stored or handled. The product should only be stored and handled in areas with intrinsically safe electrical classification.
- Advice on protection against fire and explosion** : Hydrocarbon liquids including this product can act as a non-conductive flammable liquid (or static accumulators), and may form ignitable vapor-air mixtures in storage tanks or other containers. Precautions to prevent static-initated fire or explosion during transfer, storage or handling, include but are not limited to these examples:
- (1) Ground and bond containers during product transfers. Grounding and bonding may not be adequate protection to prevent ignition or explosion of hydrocarbon liquids and vapors that are static accumulators.
 - (2) Special slow load procedures for "switch loading" must be followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil or diesel) is loaded into tanks previously containing low flash point products (such gasoline or naphtha).
 - (3) Storage tank level floats must be effectively bonded.
- For more information on precautions to prevent static-initated fire or explosion, see NFPA 77, Recommended Practice on Static Electricity (2007), and API Recommended Practice 2003, Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents (2008).
- Dust explosion class** : Not applicable
- Requirements for storage areas and containers** : Keep away from flame, sparks, excessive temperatures and open flame. Use approved containers. Keep containers closed and clearly labeled. Empty or partially full product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose containers to sources of ignition. Store in a well-ventilated area. The storage area should comply with NFPA 30 "Flammable and Combustible Liquid Code". The cleaning of tanks previously containing this product should follow API Recommended Practice (RP) 2013 "Cleaning Mobile Tanks In Flammable and Combustible Liquid Service" and API RP 2015 "Cleaning Petroleum Storage Tanks".

Advice on common storage : Keep away from food, drink and animal feed. Incompatible with oxidizing agents. Incompatible with acids.

Other data : No decomposition if stored and applied as directed. Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

| List | Components | CAS-No. | Type: | Value |
|----------|----------------------------|------------|----------|--------------------------|
| OSHA | Benzene | 71-43-2 | TWA | 1 ppm |
| | | 71-43-2 | STEL | 5 ppm |
| | | 71-43-2 | OSHA_ACT | 0.5 ppm |
| OSHA Z1 | Xylene | 1330-20-7 | PEL | 100 ppm 435 mg/m3 |
| | Ethanol; Ethyl alcohol | 64-17-5 | PEL | 1,000 ppm 1,900 mg/m3 |
| | Naphthalene | 91-20-3 | PEL | 10 ppm 50 mg/m3 |
| | Cyclohexane | 110-82-7 | PEL | 300 ppm 1,050 mg/m3 |
| | Ethylbenzene | 100-41-4 | PEL | 100 ppm 435 mg/m3 |
| | Heptane [and isomers] | 142-82-5 | PEL | 500 ppm 2,000 mg/m3 |
| | N-hexane | 110-54-3 | PEL | 500 ppm 1,800 mg/m3 |
| ACGIH | Toluene | 108-88-3 | TWA | 50 ppm |
| | Xylene | 1330-20-7 | TWA | 100 ppm |
| | | 1330-20-7 | STEL | 150 ppm |
| | Ethanol; Ethyl alcohol | 64-17-5 | TWA | 1,000 ppm |
| | Trimethylbenzene | 25551-13-7 | TWA | 25 ppm |
| | Isopentane; 2-Methylbutane | 78-78-4 | TWA | 600 ppm |
| | Naphthalene | 91-20-3 | TWA | 10 ppm |
| | | 91-20-3 | STEL | 15 ppm |
| | Benzene | 71-43-2 | TWA | 0.5 ppm |
| | | 71-43-2 | STEL | 2.5 ppm |
| | Pentane | 109-66-0 | TWA | 600 ppm |
| | Cyclohexane | 110-82-7 | TWA | 100 ppm |
| | Ethylbenzene | 100-41-4 | TWA | 100 ppm |
| | | 100-41-4 | STEL | 125 ppm |
| | Heptane [and isomers] | 142-82-5 | TWA | 400 ppm |
| 142-82-5 | | STEL | 500 ppm | |
| N-hexane | 110-54-3 | TWA | 50 ppm | |

Engineering measures : Use adequate ventilation to keep gas and vapor concentrations of this product

| | |
|---------------------------------|--|
| | below occupational exposure and flammability limits, particularly in confined spaces. Use only intrinsically safe electrical equipment approved for use in classified areas. |
| Eye protection | : Safety glasses or goggles are recommended where there is a possibility of splashing or spraying. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Hand protection | : Gloves constructed of nitrile or neoprene are recommended. Consult manufacturer specifications for further information. |
| Skin and body protection | : If needed to prevent skin contact, chemical protective clothing such as of DuPont TyChem®, Saranex or equivalent recommended based on degree of exposure. Flame resistant clothing such as Nomex ® is recommended in areas where material is stored or handled. |
| Respiratory protection | : A NIOSH/ MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited. Refer to OSHA 29 CFR 1910.134, ANSI Z88.2-1992, NIOSH Respirator Decision Logic, and the manufacturer for additional guidance on respiratory protection selection. Use a NIOSH/ MSHA-approved positive-pressure supplied-air respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection. |
| Work / Hygiene practices | : Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure. Use good personal hygiene practices. Avoid repeated and/or prolonged skin exposure. Wash hands before eating, drinking, smoking, or using toilet facilities. Do not use as a cleaning solvent on the skin. Do not use solvents or harsh abrasive skin cleaners for washing this product from exposed skin areas. Waterless hand cleaners are effective. Promptly remove contaminated clothing and launder before reuse. Use care when laundering to prevent the formation of flammable vapors which could ignite via washer or dryer. Consider the need to discard contaminated leather shoes and gloves. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|----------------------------------|---|
| Form | : Liquid |
| Appearance | : Clear, straw colored |
| Odor | : Characteristic hydrocarbon-like |
| Flash point | : -45 °C (-49 °F) |
| Auto Ignition temperature | : 257.22 °C (495.00 °F) |
| Thermal decomposition | : No decomposition if stored and applied as directed. |
| Lower explosive limit | : 1.3 %(V) |
| Upper explosive limit | : 7.6 %(V) |
| pH | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : 85 to 437 °F (39 to 200 °C) |

| | |
|--|--|
| Vapor Pressure | : 345 - 1,034 hPa at 37.8 °C (100.0 °F) |
| Relative Vapor Density | : Approximately 3 to 4 |
| Density | : 0.8 g/cm ³ |
| Water solubility | : Negligible |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : No data available |
| Percent Volatiles | : 100 % |
| Conductivity (conductivity can be reduced by environmental factors such as a decrease in temperature) | Hydrocarbon liquids without static dissipater additive may have conductivity below 1 picoSiemens per meter (pS/m). The highest electro-static ignition risks are associated with "ultra-low conductivities" below 5 pS/m. See Section 7 for sources of information on defining safe loading and handling procedures for low conductivity products. |

SECTION 10. STABILITY AND REACTIVITY

| | |
|---|---|
| Conditions to avoid | : Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources. |
| Materials to avoid | : Strong oxidizing agents. Peroxides. Strong acids. |
| Hazardous decomposition products | : Carbon monoxide, carbon dioxide and noncombusted hydrocarbons (smoke). Contact with nitric and sulfuric acids will form nitroresols that can decompose violently. |
| Thermal decomposition | : No decomposition if stored and applied as directed. |
| Hazardous reactions | : Keep away from oxidizing agents, and acidic or alkaline products. Hazardous polymerization does not occur. |

SECTION 11. TOXICOLOGICAL INFORMATION

| | |
|----------------------------------|--|
| <u>Carcinogenicity</u> | |
| NTP | : Naphthalene (CAS-No.: 91-20-3) Benzene (CAS-No.: 71-43-2) |
| IARC | : Gasoline, natural; Low boiling point naphtha (CAS-No.: 8006-61-9) Naphthalene (CAS-No.: 91-20-3) Benzene (CAS-No.: 71-43-2) Ethylbenzene (CAS-No.: 100-41-4) |
| OSHA | : Benzene (CAS-No.: 71-43-2) |
| CA Prop 65 | : WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. Toluene (CAS-No.: 108-88-3) Benzene (CAS-No.: 71-43-2) |
| Acute oral toxicity | : LD50 rat Dose: 18.8 mg/kg |
| Acute inhalation toxicity | : LC50 rat |

Dose: 20.7 mg/l
Exposure time: 4 h

Skin irritation : Irritating to skin.

Eye irritation : Irritating to eyes.

Further information : Liver and kidney injuries may occur.
Components of the product may affect the nervous system.
IARC has determined that gasoline and gasoline exhaust are possibly carcinogenic in humans. Inhalation exposure to completely vaporized unleaded gasoline caused kidney cancers in male rats and liver tumors in female mice. The U.S. EPA has determined that the male kidney tumors are species-specific and are irrelevant for human health risk assessment. The significance of the tumors seen in female mice is not known. Exposure to light hydrocarbons in the same boiling range as this product has been associated in animal studies with effects to the central and peripheral nervous systems, liver, and kidneys. The significance of these animal models to predict similar human response to gasoline is uncertain.
This product contains benzene. Human health studies indicate that prolonged and/or repeated overexposure to benzene may cause damage to the blood-forming system (particularly bone marrow), and serious blood disorders such as aplastic anemia and leukemia. Benzene is listed as a human carcinogen by the NTP, IARC, OSHA and ACGIH. Acute toxicity of benzene results primarily from depression of the central nervous system (CNS). Inhalation of concentrations over 50 ppm can produce headache, lassitude, weariness, dizziness, drowsiness, over excitation. Exposure to very high levels can result in unconsciousness and death.

Component:

Gasoline, natural; Low boiling point naphtha 8006-61-9

Acute oral toxicity: LD50 rat
Dose: 18.8 mg/kg

Acute inhalation toxicity: LC50 rat
Dose: 20.7 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.
Result: Mild skin irritation

Eye irritation: Classification: Irritating to eyes.
Result: Moderate eye irritation

Toluene 108-88-3

Acute oral toxicity: LD50 rat
Dose: 636 mg/kg

Acute dermal toxicity: LD50 rabbit
Dose: 12,124 mg/kg

Acute inhalation toxicity: LC50 rat
Dose: 49 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.
Result: Mild skin irritation
Prolonged skin contact may defat the skin and produce dermatitis.

Eye irritation: Classification: Irritating to eyes.
Result: Mild eye irritation

Xylene 1330-20-7

Acute oral toxicity: LD50 rat
Dose: 2,840 mg/kg

Acute dermal toxicity: LD50 rabbit
Dose: ca. 4,500 mg/kg

Acute inhalation toxicity: LC50 rat

Dose: 6,350 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.
Result: Mild skin irritation
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.
Eye irritation: Classification: Irritating to eyes.
Result: Mild eye irritation

Ethanol; Ethyl alcohol

64-17-5

Acute oral toxicity: LD50 rat
Dose: 6,200 mg/kg

Acute dermal toxicity: LD50 rabbit
Dose: 19,999 mg/kg

Acute inhalation toxicity: LC50 rat
Dose: 8,001 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.
Result: Mild skin irritation
Prolonged skin contact may cause skin irritation and/or dermatitis.
Eye irritation: Classification: Irritating to eyes.
Result: Mild eye irritation
Mild eye irritation

Naphthalene

91-20-3

Acute oral toxicity: LD50 rat
Dose: 2,001 mg/kg

Acute dermal toxicity: LD50 rat
Dose: 2,501 mg/kg

Acute inhalation toxicity: LC50 rat
Dose: 101 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.
Result: Mild skin irritation

Eye irritation: Classification: Irritating to eyes.
Result: Mild eye irritation

Carcinogenicity: N11.00422130

Benzene

71-43-2

Acute oral toxicity: LD50 rat
Dose: 930 mg/kg

Acute inhalation toxicity: LC50 rat
Dose: 44 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.
Result: Mild skin irritation
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.
Eye irritation: Classification: Irritating to eyes.
Result: Risk of serious damage to eyes.

Pentane

109-66-0

Acute oral toxicity: LD50 rat
Dose: 2,001 mg/kg

Acute inhalation toxicity: LC50 rat
Dose: 364 mg/l
Exposure time: 4 h

Skin irritation: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.
Eye irritation: Classification: Irritating to eyes.
Result: Mild eye irritation

| | | |
|------------------------------|----------|--|
| Cyclohexane | 110-82-7 | <p><u>Acute dermal toxicity:</u> LD50 rabbit Dose: 2,001 mg/kg</p> <p><u>Acute inhalation toxicity:</u> LC50 rat Dose: 14 mg/l Exposure time: 4 h</p> <p><u>Skin irritation:</u> Classification: Irritating to skin. Result: Skin irritation</p> <p><u>Eye irritation:</u> Classification: Irritating to eyes. Result: Mild eye irritation</p> |
| Ethylbenzene | 100-41-4 | <p><u>Acute oral toxicity:</u> LD50 rat Dose: 3,500 mg/kg</p> <p><u>Acute dermal toxicity:</u> LD50 rabbit Dose: 15,500 mg/kg</p> <p><u>Acute inhalation toxicity:</u> LC50 rat Dose: 18 mg/l Exposure time: 4 h</p> <p><u>Skin irritation:</u> Classification: Irritating to skin. Result: Mild skin irritation</p> <p><u>Eye irritation:</u> Classification: Irritating to eyes. Result: Risk of serious damage to eyes.</p> |
| Heptane [and isomers] | 142-82-5 | <p><u>Acute oral toxicity:</u> LD50 rat Dose: 15,001 mg/kg</p> <p><u>Acute inhalation toxicity:</u> LC50 rat Dose: 103 g/m³ Exposure time: 4 h</p> <p><u>Skin irritation:</u> Classification: Irritating to skin. Result: Skin irritation Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.</p> <p><u>Eye irritation:</u> Classification: Irritating to eyes. Result: Mild eye irritation</p> |
| N-hexane | 110-54-3 | <p><u>Acute oral toxicity:</u> LD50 rat Dose: 25,000 mg/kg</p> <p><u>Acute dermal toxicity:</u> LD50 rabbit Dose: 2,001 mg/kg</p> <p><u>Acute inhalation toxicity:</u> LC50 rat Dose: 171.6 mg/l Exposure time: 4 h</p> <p><u>Skin irritation:</u> Classification: Irritating to skin. Result: Skin irritation</p> <p><u>Eye irritation:</u> Classification: Irritating to eyes. Result: Mild eye irritation</p> <p><u>Teratogenicity:</u> N11.00418960</p> |

SECTION 12. ECOLOGICAL INFORMATION

Additional ecological information : Keep out of sewers, drainage areas, and waterways. Report spills and releases, as applicable, under Federal and State regulations.

Component:

| | | |
|-----------------------------------|----------|--|
| Toluene | 108-88-3 | <p><u>Toxicity to fish:</u> LC50 Species: Carassius auratus (goldfish) Dose: 13 mg/l Exposure time: 96 h</p> <p><u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 11.5 mg/l Exposure time: 48 h</p> <p><u>Toxicity to algae:</u> IC50 Species: Selenastrum capricornutum (green algae) Dose: 12 mg/l Exposure time: 72 h</p> |
| Ethanol; Ethyl alcohol | 64-17-5 | <p><u>Toxicity to fish:</u> LC50 Species: Leuciscus idus (Golden orfe) Dose: 8,140 mg/l Exposure time: 48 h</p> <p><u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 9,268 - 14,221 mg/l Exposure time: 48 h</p> |
| Isopentane; 2-Methylbutane | 78-78-4 | <p><u>Toxicity to fish:</u> LC50 Species: Oncorhynchus mykiss (rainbow trout) Dose: 3.1 mg/l Exposure time: 96 h</p> <p><u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 2.3 mg/l Exposure time: 96 h</p> |
| Naphthalene | 91-20-3 | <p><u>Toxicity to algae:</u> EC50 Species: Dose: 33 mg/l Exposure time: 24 h</p> |
| Pentane | 109-66-0 | <p><u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 9.74 mg/l Exposure time: 48 h</p> |
| Cyclohexane | 110-82-7 | <p><u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 3.78 mg/l Exposure time: 48 h</p> |
| Heptane [and isomers] | 142-82-5 | <p><u>Toxicity to fish:</u> LC50 Species: Carassius auratus (goldfish) Dose: 4 mg/l Exposure time: 24 h</p> <p><u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 1.5 mg/l Exposure time: 48 h</p> |

N-hexane

110-54-3

Toxicity to fish:

LC50

Species: Pimephales promelas (fathead minnow)

Dose: 2.5 mg/l

Exposure time: 96 h

Acute and prolonged toxicity for aquatic invertebrates:

EC50

Species: Daphnia magna (Water flea)

Dose: 2.1 mg/l

Exposure time: 48 h

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal : Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14. TRANSPORT INFORMATION**CFR**

Proper shipping name : Petrol

UN-No. : 1203

Class : 3

Packing group : II

TDG

Proper shipping name : Gasoline

UN-No. : UN1203

Class : 3

Packing group : II

IATA Cargo Transport

UN UN-No. : UN1203

Description of the goods : Gasoline

Class : 3

Packaging group : II

ICAO-Labels : 3

Packing instruction (cargo aircraft) : 307

Packing instruction (cargo aircraft) : Y305

IATA Passenger Transport

UN UN-No. : UN1203

Description of the goods : Gasoline

Class : 3

Packaging group : II

ICAO-Labels : 3

Packing instruction (passenger aircraft) : 305

Packing instruction (passenger aircraft) : Y305

IMDG-Code

